

Single Mode Dual Window Wavelength Flattened Coupler

Features

Wide Bandwidth and Low Insertion
 Low Insertion Loss
 High Quality and Reliability

Applications

Fiber Distribution Network
 CATV Network
 Test Equipment

Specifications

Parameters	Unit	Values			
Center Wavelength	nm	1310 and 1550			
Operating Wavelength Range	nm	±40			
Coupling Ratio	%	01/99	05/95	10/90	50/50
Max. Insertion Loss	dB	23.5/0.3	15.2/0.4	11.3/0.6	3.6
Max. PDL	dB	0.15			
Max. Excess Loss	dB	0.10			
Thermal Stability	dB/°C	≤ 0.002 over -5 °C to +70 °C			
Min. Directivity	1X2	55			
	2X2	65			
Package Dimensions		250um Bare Fiber and dia. 3.0mmX40mm			
		900um Loose Tube and dia. 3.0mmX56mm			
		3mm Loose Cable and 90mmX16mmX9mm			
Max. Optical Power (CW)	mW	500			
Max. Tensile Load	N	5			
Fiber Type		SMF-28e Fiber			
Operating Temperature	°C	-5 to + 70			
Storage Temperature	°C	-40 to + 85			

*Above specifications are for device without connector.

*For devices with connectors, IL will be 0.3dB higher and RL will be 5dB lower.

Ordering information

SDC-①①①①-②-③③-④④-⑤⑤-⑥

①①①①: Wavelength
 3155 - 1310 & 1550nm
 SSSS - Specify

②: Port
 1 - 1X2
 2 - 2X2

③③: Coupling Ratio
 01 - 01/99
 05 - 05/95
 10 - 10/90
 50 - 50/50
 SS - Specify

④④: Connector Type on Port 1 & 2
 1 - FC/UPC
 2 - FC/APC
 3 - SC/UPC
 4 - SC/APC
 N - None
 S - Specify

⑤⑤: Fiber Jacket on Port 1 & 2
 B - 250um Bare Fiber
 L - 900um Loose Tube
 C - 3mm Loose Cable
 S - Specify

⑥: Fiber Length
 1 - 1.0m
 S - Specify